

Sound Level Meter

SL-1352

HTCTM
INSTRUMENTS

Features:

- Max & Min Measurement
- Over Range Display
- Under range display
- A & C Weighting
- FAST & SLOW response
- Analog AC/DC Outputs for connection to frequency analyzer or X-Y shaft recorder
- Datalogger function
- Adjustable Alarm Levels
- Backlight
- **USB Computer Interface** (advanced Software program for all Windows)

Technical Data:

| Basic Function | Range |
|-----------------|---|
| Accuracy | 1.4dB |
| Resolution | 0.1dB |
| Frequency Range | 31.5Hz ~8kHz |
| Dynamic Range | 50dB |
| Level Range | Low:30dB~80dB Medium:50dB~100dB High:80dB~130dB Auto: 30dB~130dB |
| Time Wiegthing | FAST (125mS),SLOW (1s) |
| Microphone | ½ inch electric condenser microphone |
| Display Update | 2 times/sec |
| Analog Output | AC/DC outputs,AC= 1Vrms,DC= 10mV/dB |

Special Function:

| | | | |
|--------------|----------|---------------------|--------------|
| Alarm | Electron | Power Supply | 1 x9VBattery |
|--------------|----------|---------------------|--------------|

- **Standard Accessories** : Gift Box with Hard Carrying Case, Manual , Battery,



Screwdriver, Audio Plug, Windscreen,
Tripod & DC 9V power supply,
HTC USB with Software

- **Dimension** : 278(H) x 76(W) x 50(D)mm