

## **SMART GLOSS METER-111**



### **Features:**

- 60° angle for semi-gloss
- Measuring mode: basic measurement, statistical measurement, continuous measurement, QC measurement (only for GQC6 software)
- Continuous mode to check uniformity over large areas
- Connect to PC, more extend functions
- Input gloss value manually
- Large touch screen operation, easy to use
- Beauty appearance, good man-machine communication interface
- Powerful functions to meet many different requirements
- Large storage to save over 1000 data
- Built-in lithium ion rechargeable battery

<b>Model</b>	<b>GLOSS-111</b>		
<b>Measure Angle</b>	60° Comply with standard ISO 2813, GB/T 9754, ASTM D 523, ASTM D 2457		
<b>Measurement Range</b>	0~300GU		
<b>Division Value</b>	0.1GU		
<b>Measurement Range</b>	0-10GU	10-100GU	100-300GU
<b>Repeatability</b>	± 0.1GU	± 0.2GU	± 0.2%GU
<b>Reproducibility</b>	± 0.2GU	± 0.5GU	± 0.5%GU
<b>Chromaticity Corresponding SOURCE</b>	<b>CORRESPONDING WITH CIE 1931(2) UNDER CIE C LIGHT</b>		
<b>Measuring Time</b>	0.5s		
<b>Dimension</b>	L*W*H : 160mm*75mm*90mm		
<b>Weight</b>	350g		
<b>Battery</b>	3200mAh Li-ion Battery, >10000 times(within 8 hours)		
<b>Viewing Screen</b>	TFT 3.5 inch, capacitive touch screen		
<b>Interface</b>	USB/RS-232		
<b>Software</b>	GQC6 Quality Control Software with QC report Printing functions and more extended functions.		
<b>Operation Temperature</b>	0~40°C (32~104°F)		
<b>Storage Temperature</b>	-20~50°C (-4~122°F)		
<b>Humidity</b>	<85% relative humidity, no condensation		
<b>Standard Accessories</b>	Power Adapter, USB cable, User Manual, CD (Including QC software), Calibration Plate		
<b>Optional Accessories</b>	Miniature Printer		
<b>Note</b>	The specifications are subject to change without Notice.		

## Smartech Inc.

F-109, Sundram Complex, Near Vadsar Bridge to Darbar Chowkdi, Opp.Ambe School, Makarpura, Vadodara - 10

PH: 2631121, 9825439692

Email: [smartechinc1@gmail.com](mailto:smartechinc1@gmail.com)